



| No | Part's Name | Material | Qt'y | Rev.Reason |
|----|-----------------------|--------------|------|-------------------|
| 1 | M-Body | SCS13 | 1 | |
| 2 | M-Handl | SCS13 | 1 | |
| 3 | 1.0S Body | SUS316L | 1 | Electro-Polishing |
| 4 | D-Main Shaft Ass'y | SUS316L+PTFE | 1 | Electro-Polishing |
| 5 | Diaphragm | PTFE/FKM | 1 | |
| 6 | JIS 10K 40A Flange | SUS316L | 1 | Electro-Polishing |
| 7 | 1.0S 45 ° Sweep Elbow | SUS316L | 1 | Electro-Polishing |

| | | | | | | | | | | |
|------------|----------|-------|------|------|-----|-------------------|------------|------------|-------------------|-----------------|
| 指示無き R面 | 普通寸法許容公差 | 区分 | 精級 | 中級 | 粗級 | I.O. Technologies | MODEL | | SD-B-25 M-1-2-0-9 | |
| | | —6 | 0.05 | 0.08 | 0.2 | | MATERIAL | DATE | TITLE | Diaphragm Valve |
| | | —18 | 0.08 | 0.10 | 0.3 | | 2003/03/17 | DESIGNED | DRAWING No. | T00312 |
| | | —50 | 0.10 | 0.15 | 0.4 | | APPROVED | CHECKED | S.OHTSUKA | Free |
| R = | | —180 | 0.20 | 0.30 | 0.8 | | | | | |
| 指示無き C面 | | —500 | 0.30 | 0.50 | 1.2 | | | | | |
| C = | | —1000 | 0.60 | 1.00 | 2.5 | | | | | |
| | | △x | | | | REV. | DATE | REV.REASON | CHECK | |