



No	Part's Name	Material	Qt'y	Rev.Reason
1	Actuator	SUS304	1	
2	Body	SUS316L	1	Electro-Polishing
3	D-Main Shaft Ass'y	SUS316L+PTFE	1	Electro-Polishing
4	Diaphragm	PTFE/FKM	1	
5	JIS 10K 20A Flange	SUS316L	1	Electro-Polishing
6	I.S.O-15A 45° Elbow	SUS316L	1	Electro-Polishing
7	I.S.O-15A Ferrule	SUS316L	1	Electro-Polishing

区分	精級	中級	粗級
~6	0.05	0.08	0.2
~18	0.08	0.10	0.3
~50	0.10	0.15	0.4
~180	0.20	0.30	0.8
~500	0.30	0.50	1.2
~1000	0.60	1.00	2.0

指示無き R面	普通寸法許容公差	△× 1	2021.10.14	アクチュエータ改良によりエア供給継手位置変更(11mm)	S. OHTA
R=		REV.	DATE	REV.REASON	CHECK
指示無き C面					
C=					

I.O. Technologies		MODEL	SD-B-15 A-1-2-0-FG
MATERIAL	DATE	TITLE	
	2004/10/12	Diaphragm Valve (Tank)	
APPROVED	CHECKED	DESIGNED	DRAWING No.
K. OHTA		S. OHTSUKA	TS0003
			1/1